



Provides Same Lethality as Turret at Less than Half the Price and Weight





R800S

GREATEST LETHALITY ON AN UNTURRETED SYSTEM

The R800S is a heavy gimbal RWS that mounts the Bushmaster Mk44S 30x173mm canon, plus mounting points for Anti-Tank Guided Missiles (ATGM), Surface-to-Air Missiles (SAM) and additional effectors. Employing the same common interface as our family of RWS, the R800S is intended for customers requiring a lethality upgrade without compromising payload or making the extensive modifications required of a full turret system. The R800S offers protection levels from STANAG Level 2 to 4 and delivers turret-level direct firepower for 50% of the weight and cost.



| SPECIFICATIONS | BASELINE SYSTEM | OPTIONS |
|----------------------------|---|---|
| Primary Armament | Bushmaster Mk44S 30 X 173 mm Cannon | Bushmaster M230LF 30 mm x 113 mm cannon |
| Secondary Armament | Mk52 7.62 mm chain gun or M240 7.62 mm machine gun | M2 .50 cal machine gun M134 7.62 mm chain gun |
| Missile | 1 x Javelin™ or 2 x SPIKE™ (pod) | 4 x Javelin™ (2 x pods either side) 4 x SPIKE™ (2 x pods either side) 1 x 2.75″ APKWS rocket pod 2 x Stinger™ pods |
| Ammunition Load (30 mm) | 200 rds (2 x containers), dual feed | 300+ rds (2 x containers), dual feed |
| Ammunition Load (7.62 mm) | 1000 rds | 2000 rds |
| Sensor Unit | Continuous zoom day camera Continuous zoom thermal camera Eye-safe Class 1 laser finder | Full meteorological sensor suite 4-axis stabilization |
| Ballistic Protection | Basic add-on armor kit: STANAG level II to sensor units, ammunition and electronics | STANAG level II/III/IV to all systems |
| Elevation Range | +60 degrees -15 degrees | |
| Height | 39 in/1000 mm (to top of main gun) | |
| Length (Base) | 47 in/1200 mm | |
| Length (Overall) | 135 in/3430 mm | |
| Width (Base) | 47 in/1200 mm | |
| Width (Overall) | 55 in/ 1400 mm (not including missiles or other side attachments) | |
| Weight (No armor) | 1765 lbs/800 kg (includes weapons and an ammunition load of 150 x 30 mm rds plus 500 x 7.62 mm rds) | |

FOR MORE INFORMATION:

EMAIL DEFENSE@EOSDSUSA.COM VISIT EOSDSUSA.COM